



RO/PRAYAGRAJ/04/P&E/2023-24/78

Date: - 01.09.2023

TENDER FOR FURNISHING, ELECTRICAL & DATA WORK OF RAMNAGAR BRANCH, DISTRICT - PRAYAGRAJ.

Baroda UP Bank Regional Office Prayagraj, 3 D Tashkant Marg Civil Line, invites sealed tender for furnishing for our **Ramnagar** branch (Dist- Prayagraj) from the empanelled Furnishers of Baroda UP Bank, Head Office, Buddh Vihar Taramandal Gorakhpur-273016 (U.P).

1. Tender issuing date

: 01.09.2023

2. Last date for submission of tender

: 21.09.2023 at 4:00 PM

3. Date of opening of tender

: 21.09.2023 at 5:00 PM

4. Contact Number

: 9793138316

5. Tender to be address to

: The Regional Head Baroda UP Bank,

Regional Office- Prayagraj, 3D Tashkant Marg Civil Line,

211001

Terms and condition of tender:

- Ø Rates should be quoted on the space provided in <u>annexure attached only</u>. No other sheet/form should be used for quoting rates.
- Ø The competent authority (bank) does not bind themselves to accept the lowest or to give any reasons for its decision of acceptance or rejection of tenders.
- O Incomplete in any respect or conditional tender shall liable to be rejected.
- Ø Rates quoted only by bank's empanelled vendors will be consider/accepted.

Other conditions:

- O The registration number of the firm along with GST no. allotted by the authorities must be submitted.
- O PAN NUMBER of the firm allotted by the income tax authorities should be submitted (without which the vendor's bid would become invalid and shall be liable to reject)
- O Conditional tenders shall not be accepted on any ground and shall be rejected straight.
- O Any deviation of the conditions given by the purchaser will not be accepted and bid will be rejected without assigning any reasons.
- O If any clarification is required the same should be obtained before submitting the bid.
- O The entire document must be signed with the seal and attached as mark of acceptance of terms and condition.

Regional Office: 3 D Tashkant Marg Civil Line Prayagraj 211001 (U.P.) E-mail: roalla@barodauprrb.co.in; Fax-0532-2407653 Mo.7311121755,7311121764,







- Ø BUPB reserve the right to accept or reject any bid whole or in parts without assigning any reason thereof.
- @ Bank's decision will be final and no correspondence will be entertained in this regard.
- Ø In case of delays in submission/non submission of bids ,Bank will not assume any responsibility.
- O Bank may reject any or all quotations without assigning any reason.

Tender submission:

Submission of tenders in sealed envelope super scribing "TENDER OF FURNISHING, ELECTRIC, DATA WORK OF RAMNAGAR BRANCH" addressed to "The Regional Manager Baroda UP Bank, Regional Office- Prayagraj, 3D Tashkant Marg Civil Line; 211001", Complete in all respect latest by 4.00 PM dated- 21.09.2023 Tenders received after that shall not be entertained.

Tender must be submitted through hand to hand or through registered post.

Evaluation of tender:

Quoting incredibly low value of items with a view of subverting the tender process shall be rejected straight away.

Yours faithfully,

(Sushil Kumar)

Regional Head Prayagraj – Region Ref No.: BA/01/5010/2023

DETAILED ESTIMATE / SPECIFICATION FOR BILL OF QUANTITIES OF FURNISHING WORK FOR BARODA UP BANK BRANCH AT RAMNAGAR

Sl.no	Description of items	Unit	Qty.	Rate	Amount
1	False ceiling (Armstrong)	Sft	0		
	Providing and fixing in position false ceiling in Armstrong 600 x 600 mm x 15/16 mm dune supreme RH 99 prima tile with regular edge framework as specified by Armstrong Co. with suspenders wherever required. Maing necessary framework for A.C. ducting if any and necessary cutouts for diffusers and light fittings, taping and finishing to proper line and level including making grooves and trap doors for A.C. unit in 18 mm thick M.R. grade plywood with stainless steel hinges and licks with moulding 1" x 1" for edges including finishing with white plastic emulsion paint etc. complete in all respect. (Note:-only the plan area will be measured for payment no extra payment will be made for cutouts, grooves moulding etc.)				
2	False Ceiling (Gyp Board)	Sft	0		
	P/F Suspended False Ceiling Gyp Board with G.I. Perimeter channels G.I. Intermediate Channels Etc. properly suspended from ceiling with Nylon/G./l. strips sleeves and Screws 12.5 Mm tapered edgeg Gyp board (confirming To I.S.2095-1982)ceiling tiles to be screw Fixed to the ceiling section with 25mm dry Wall screw mechanically at 230C/C and Finished with jointing compound paper tapeAnd two coars of primer and two coats of plastic paint complete as per design Including perimeter channels required for Light fitting cut out Grill diffusers etc.				
3	PAINTING WORK with Two Coat POP Base (Only Hall Area)	Sft	1540		
,	Painting on undecorated / decorated wall and ceiling surfaces with two or more coats of acrylic emulsion (Asian/Berger make) (as / shade approved by the Architect) of approved brand. It shall include for preparing the surfaces clean, even and smooth with thoroughly brushing with broom, scratching with patti and sand papering respectively, so that the surfaces are free from oil, grease, dirt, mortar droppings & other foreign and loose matter. It shall also include for preparing the surface and filling of holes with plaster of paris before priming coat of whiting / approved primer. The rate shall include cost of all materials such as plaster of paris, whiting /primer, glue (Fevicol), indigo / stainer, brushes, sand paper, patti, dhoti, broom stick, clean water with storage and other containers, labour, scaffolding / ladder charges, cleaning of floors and other sundries etc., all complete to the satisfaction of the Architect.				
4	Entrance Door Branch	Sft	80		

	Description of items	Uni	t	Qty.	Rate	Amount
	Providing fabricating & fixing in position twin –style door at Main Entrance made of anodized/powder coated Aluminum sections of size 100mm height x 50mm thick aluminum bottom rail, 100mm x 50mm thick vertical and top rail 100mm x 50mm thick lock rail floor spring of ISI make, clip sections and 12mm thick glass(Modi/Saint Gobain make) including fixing the frame to brick wall/RCC/wooden surfaces with necessary fasteners to have prope fixity including all incidentals etc complete. Glass to be fixed in the grooves of the aluminum sections with necessary materials/beading etc. The job also includes cost of providing & fixing heavy duty double action hydraulic floor spring (ISI mark) in the floor, fixing the door on it, including necessary fixing materials on the lintel/bottom, bolts, locks & satin finish stainless steel decorative tubular handles(approx.300mm long) on both faces complete as per drawing and instructions. All members to be 16 gauge. The vertical shutter rail to house wool packing to act as a sealant for a gap between shutter and frame fixed glazing. The rate should also include cost for decorative etching on the glass.	T				
5	Computerised Ledger & Cash Counter					
	Providing and placing in position ledger counter with top, vertical sides/dividers, skirting and fascia made out of 19mm thick water proof board with 1mm thick laminate (as/shade approved by the Architect) on all exposed surfaces. It shall also have 75mm x 40mm teak wood runners below the top and for footrest below. Every unit shall be provided with a side unit (size - W-500mm, H-750mm, D-500mm approx.), consisting of 150 mm deep drawer at top and a cabinet with open able/hinged shutter below.					
	. The fascia of drawer and shutter of cabinet below shall be made out 19mm thick water proof board with 1mm thick laminate (as/shade approved by the Architect) and sides and bottom of drawer shall be made out of 12mm thick water proof ply. The side unit shall have CAM locks, handles, guides, sliding units, hinges, magnetic catcher's etc. of approved make. Every unit shall be provided with a keyboard drawer unit (size - W-550mm, H-100mm, D-300mm approx.) below. The counter shall have 100mm deep fascia, below the top, in which keyboard drawer unit shall be adjusted.					
	It shall be made out 19mm thick water proof board with 1mm thick laminate (as/shade approved by the Architect) and sides and bottom of drawer shall be made out of 12mm thick water proof ply. The unit shall have CAM locks, handles, guides, sliding units etc. of approved make. The job shall include for 6mm x 6mm grooves in between sides and open able drawers and hinged shutters. All the exposed edges of water proof board and ply shall be provided with 5mm thick teak wood/hard wood lipping. All teak wood surfaces shall be melamine polished and other internal surfaces shall be painted with two coats of synthetic enamel over one coat of primer, all complete to the satisfaction of the Architect.					
F	ligh Level	264	_			
	ligh level (two levels) Computerised cash counter.	Rft	5			
L	ower level top shall be 900mm wide and at 750mm level from floor upper level top shall be 250mm wide (and at 1150 mm level from					
-	ow Level					

	Description of items	Unit	Otre		
	Low level (two levels) C-		Qty.	Rate	Amoun
	Low level (two levels) Computerised ledger counter including 1.5 f	t			
	edges of the glass to be machine polished.				
	1 (2.7%) #1.230 #10. 50453945705	1			
		1 1			
I	ower level top shall be 900mm wide and at 750mm level from floor				
8	k upper level top shall be 150mm wide and at 750mm level from floor loor				
f	loor loor and at 900mm level from	-			
-		1			
6 S	olid full height partition both side Laminated				
L	or unglazed partitions no glazing to be significant.	Sft	95		
0	ther specifications as below 9.				
1/2	note i in an a sector 9.				
(1)	note: in case of false ceiling, the vertical TW members to be fixed ith pucca ceiling but the area of				
th	ne false ceiling only.)				
P:	artly glazed partition 5				
to	artly glazed partition for cash cabins (Wall side partition not	Sft	85		
D	PCOrotivo Call (10	010	00		
170	ecorative Grill (12mm thk)-hexagonal opening as per instruction Bank's Engineer/Architect) All companies as per instruction				
LI	pping.		1		
Pro	oviding and fixing of Cash England				
An	oviding and fixing of Cash Enclosures at height of 7'-4" with				
2"3	nodized aluminium frame work, heavy sections (2mm thickness) of				
BU	(1.5", spacing of 2'0"x2'0" on bothsides and covered 6mm thick	1			
E-	VR plywood finished with 1mm thick laminate of blue, red colours skriting & borders Partition chell by			1	
IOT	skriting & borders.Partition shall have provision for opening and	1			
191	mm BWR plywood tray for challan receiving purpose. Cost				
inc	lude aluminium grill and fixed with teak wood beading and duco				
2'6'	"x7'0", fixed in the partition Door at 11 in				
and	"x7'0", fixed in the partition. Door shall have teak wood beading				
of s	I lipping with duco paint. Door finished with 1mm thick laminate				
bot	white colour for base and red & blue for skirting of approved				
Pat	tern. Door shall have 8mm glass fixed with teak wood beading	- 1			
thre	t also include cash transporters.				
Cos	t also include cash transaction ensures to the and handles.				
door	t also include cash transaction opening shall be provided with arrangements made with BWR plywood frame work finished by inate, duco paint and locking provided with a state of the state o				
lam	inate duce paint and by BWR plywood frame work finished by		-		
tran	inate, duco paint and locking system. Cost include wastages,				
lood	sports, loading, unloading charges, labours, materials, tools,				
Arch	litect.				
11					
1					
Solid	till 4'-0" then Aluminium Decorative Grill height till 7' On.				
Solid	till 4'-0" then Aluminium Decorative Grill height till 7'-0"then				
Solid	till 4'-0" then Aluminium Decorative Grill height till 7'-0"then				
Partl	y glazed low height partition				
Partl Same	y glazed low height partition	Sft	135		
Partl Same	y glazed low height partition	Sft	135		
Partl Same	y glazed low height partition specification as in 1 but P/F half height partition of height 4'- th wooden leminate till 2' 0"	Sft	135		
Partl Same 6" wi	y glazed low height partition specification as in 1 but P/F half height partition of height 4'- th wooden laminate till 3'-0" and 1'-6" height 12 mm thick secured with D brackets including	Sft	135		
Partl Same 6" wi	y glazed low height partition	Sft	135		
Partl Same 6" wi	y glazed low height partition specification as in 1 but P/F half height partition of height 4'- th wooden laminate till 3'-0" and 1'-6" height 12 mm thick secured with D brackets including	Sft	135		
Partl Same 6" wi	y glazed low height partition specification as in 1 but P/F half height partition of height 4'- th wooden laminate till 3'-0" and 1'-6" height 12 mm thick secured with D brackets including	Sft	135		

	Description of items	Unit	Qty.	Rate	Amount
	Providing and fixing Column Panelling consisting of 2" x1 " 1 gauge section placed at 2'0x2'-0" horizontally and vertically wit Unannodised Allumnium size 1.5mm thick of JINDAL/ INDA confirming to ISI 303 standard as internal frame structure (as posite requirement) framework. The framing shall be fixed with wit 8mm thick MR grade ply + 6 mm MDF of approved make firml screwd to the aluminium frame on either side finished with 1mm to (high glossor texture) laminate as per approved sample. Iter includes providing and fixing 12x12mm steem beech wood beading	h L er h y	60		
1	making 6 mm grooves complete with polish & melamine spra- finish on wood surface/grooves as per architectural drawing- finished with 1mm thick laminate. Item includes providing and fixing 100mm wide skirting of 1mm thick mettallic laminate as per approved sample. Note: Surface measurement for one face & visible areas below false ceiling will be made for payment.	1			
0 <u>1</u>	Manager's table + Side Table with 12mm thk glass top				
	Providing and fixing in position manager's table of size 6'-0"x2'6" as	Each	1		
h k F fr	per drawing no. including side storage (credenza)by using 25 mm hick plywood for top and 18 mm thick plywood for all other orzontal and vertical members. Telescopic CPU stand/ready made eyboard tray shall be provided of approved model and make. ootrest made with TW member of size 4"x1 ½ " finished with rench polish.as per.				
al st fir las ta TV en ne	drawing shall be provided. Facia of side storage(credenza) shall be mished with 1 mm thick laminates as shown in the drawing and 1 other sides shall be finished with white enamel paint. The side orage (credenza) shall be provided with handles (stainless steel nish) and channels as per approval of the project consultant/bank all exposed plywood surfaces to be finished with 1 mm thick minates of approved make and shade and all exposed edges of ble top and ply verticals to have 1" x ¼" TW lipping, all exposed vection to be melamined and internal surfaces to have white amel paint as directed. Item to include plywood boxing, all cressary hardware and fittings in stainless steel finish, lipping to edgs etc. complete in all respect.				
Of:	ficer table + Side Table with 12mm thk glass top 0"x2'-6")+Side table	Each	1		
	me specification as above				
Ful	ll height storage / low height storage/ back storage	0.0			
Pro	viding and fixing in position full height stores ()	Sft	95		
and with side	i (10) respectively using plywood of required thickness finished in 1 mm thick laminates as shown in the drawing and all other as shall be finished with white enamel paint as detailed therein.				a X
Ine	storage units shall be provided with handles (stainless steel sh) as per approval of the project consultant/bank.				

Sl.no	Description of items	Unit	Qty.	Rate	Amount
	All exposed plywood surfaces to be finished with 1 mm thick. Laminate of approved make and shade and all exposed edges of plywood to have 1"x1/4" TW lipping all exposed TW section to be melamined in matching colour laminate and internal surfaces to have white enamel paint as directed attemption include all necessary hardware an fittings in stainless steel finish and Godrej multi purpose locks including magnetic ball catcher etc. complete in all respect.				
13	12 MM THICK GLASS FOR CASH CABIN & COUNTER				
	Providing & fixing 12 m.m. glass in front of cash cabin with brass clamps including cut out for passing currency as/details. The edges of the glass to be machine polished.	Sq. ft.	50		
14	Suggestion box	No	1		
15	Public writing wall stand (including cost of fitting) 36"x16"x9" 19mm Board, 1.00 mm thick mica, teak wood beeding, Polish/Paint with fitting.	No	1		
16	Check drop box	No.	1		
			Tota	l Rs.	

Not: GST Will be charged Extra

		For - Bharat & Associates
SI. No.	Materials	Approved manufacturers / suppliers
1	Paint	I.C.I. (Dulex - Duco) / Asian paints / Goodlac Nerolac
2	Plywood	BWR- Century/Green/Archid only Premium quality
3	Wood preservative	BWR- Century/Green /Archid only Premium quality
4	False ceiling	Armstrong , Indian gypsum board
5	Laminates	Sunmica/ Archid/Century/Green 1mm thick as per bank approved color
6	Screws	G.K.W./Nettle fold
7	Adhesive	Fevicol SH
8	Night latch	Godrej
9	Locks	Godrej
10	Aluminium door frame	Jindal
11	Glass	Modi/Asahi/Saint Gobain
12	Aluminium cladding	Eurobond/Altobond/Alukbond
13	Key board drawer	EBCO
14	Telescopic CPU stand	EBCO
15	Cable organiser (wire manager)	EBCO
16	Vitrified tiles	Jhonsions Perlto
17	Venetion blind	Vista, Luxaflex

Note: Plywood mentioned in the drawings as well as in bill of quantities should be IS: 710 BWR- Century/Green only Premium quality.

Bharat and Associates.
Architects, Engineers, Interiors &
Landscape Designers,
Shop no-1,First Floor,Jeevan Plaza
Viram Khand-5, Gomti Nagar,Lucknow-226010

PROJECT - ESTIMATE FOR ELECTRICAL WORKS.

BANK - BARODA UP BANK

BRANCH-RAM NAGAR

NICI	PARTICULARS	Unit	Qty	Rate	Amount
NO	A -Electrical wiring (All switches to be Modular type - Anchor/ Havells				
1	or equivalent approved by architect)				
7.735	·				
	Light & Fan points Supply & Installation of concealed point wiring using 600v grade 3x1.5				
1	Sq.mm copper conductor PVC insulated wires (with proper R,Y,B color				
	code) pulled through heavy gauge 19mm PVC conduit pipe heavy duty				
	concealed in wall/ floor/ panelling/ partitions or above false ceiling as				
	per requirement including 2 Nos. 2.5 sqmm circuit wires from the				
	relevant DB and also including 1.5 sqmm green color copper earth wire				
	and switch plate, switches, etc. as approved by the Bank's				
	Engineer/Architect. All switch & sokets shall be modular type				
	complete with cover plate & GI/ MS box. The work shall also include				
	for cutting chase for conduits and moulded boxes, if required, in the				
	wall/ floor (Without damaging the building/wall) along with clamping				
	the conduit at every 600mm interval & finally finishing the surface &				
	matching the same with the existing surface. The rate should include the cost of all materials, labour, T&P, taxes & levies, scaffolding,				
	shifting of furniture, carting away the debris and cleaning the floor				
	Light points + AFF points including the cost of 6A switch	Point	25		
a	Ceiling Fan Point including the cost of 6A Switch along with electronic				
b	regulator	Point	3		
	Wall Fan Point along with 6A switch	Point	8		
d	6A switch & Socket on SDb	Point	6		
2	RAW POWER POINT				
2	Single Power Points - Supply & Installation of point wiring for Raw				
	power plug points on workstations / table for computers using 2 X2.5 +				
	1x1 5 So mm copper conductor PVC sheathed flexible wire pulled				
	through heavy gauge 19mm PVC conduit pipe heavy duty concealed in				
	wall/ floor/ panelling/ partitions or above false ceiling as per				
	requirement. Each point consisting of 1 nos of 16A, 2/3/5 pin sockets				
	& 1 No.16A Switch wired together forming one point. The earth wire of				
	green color only. All switch & sokets shall be modular type complete	Point	6		
	with cover plate & GI/ MS box. The work shall also include for cutting				
	chase for conduits and moulded boxes, if required, in the wall/ floor				
	(Without damaging the building/wall) along with clamping the conduit at every 600mm interval & finally finishing the surface & matching the				
	same with the existing surface. The rate should include the cost of all		-		
	materials, labour, T&P, taxes & levies, scaffolding, shifting of furniture,				
	carting away the debris and cleaning the floor etc. The job shall be				
2	AIR CONDITIONING				
3	AIR CONDITIONING AIR CONDITION POINTS - Circuit wiring with 2x4.0sq.mm + 1x				
а	1.5sq.mm stranded Cu. conductor (Finolex/Anchor/Skytone) in 19mm				
	M S conduit pipe heavy duty 16swg laid & concealed in wall/ floor/				
	panelling / partitions or above false ceiling as per requirement. The job				=
	includes supply & fixing of flush mounted 4in one appliance protector				
	pre-wired, IP 20 with factory fitted 25A, 2P MCB and 25A socket	Point	0.		
	(Hagers / Siemens / ABB). The rate should include the cost of all	- Omit			
	materials, labour, T&P, taxes & levies, scaffolding, shifting of furniture,				
	carting away the debris and cleaning the floor etc. The job shall be				
	complete & to the entire satisfaction of the Bank.				
	95				
4	UPS				

Δ.	0.1 M : W" :				
A	Sub Main Wiring/ Cabling - : SITC of sub main wiring 4nos. 10 sq.mm Stranded copper wires for UPS Input from main incoming panel to incoming Db of UPS power input system etc. in 25mm dia PVC haevy duty conduit complete to the satisfaction of the bank.	JOB	1		
-	VIDO D				
В	UPS Power Input System: SITC of 4way TPN Double door Db IP 42 horizontal Complete with 1no. Incoming 32A. TP MCB and 3 x 32A 2P MCB's to regulate supply for UPS complete in all respect as required and to the satisfaction of the bank.	Set	1		
_					
C	Wiring for UPS Input & UPS Output (For both Critical 2Kva & Non-Critical 3Kva UPS) with 2x4.0sq.mm + 1x 1.5sq.mm stranded Cu. conductor (Finolex /Anchor /Skytone) to be laid in 19mm PVC pipe heavy duty/ Flexible pipe laid & concealed in wall/ floor/ panelling/ partitions or above false ceiling as per requirement. The rate should include the cost of all materials, labour, T&P, taxes & levies, scaffolding, shifting of furniture, carting away the debris and cleaning the floor etc. The job shall be complete & to the entire satisfaction of the	JOB	1		
D	S/F of 32A 2P MCP in 2 year matellies to a 1 11				
D	S/F of 32A 2P MCB in 2way metallic box including proper connectionbs thru lugs. Both the Db's shall be inter looped- Qty included in item 3. (2nos. For ATM and 2nos. For Branch)	Each	1		
E	LIDS Output Danie Did it is a				
Е	UPS Output Power Distribution System: SITC of 12 way SPN Db Double door IP -43 Siemens make with 32A DP 10kA MCB and 09 nos. SP 10kA MCB complete in all respect and as required & to the satisfaction of the bank. Siemens/ L&T/ MDS/ Schnider	Set	1		
F	Y WY Y				
1	Input Wiring for UPS Db's with 2x4.0sq.mm + 1x 1.5sq.mm stranded Cu. conductor (Finolex / Anchor / Skytone) to be laid in 19mm PVC pipe heavy duty/ Flexible pipe laid & concealed in wall/ floor/ panelling/partitions or above false ceiling as per requirement. The rate should include the cost of all materials, labour, T&P, taxes & levies, scaffolding, shifting of furniture, carting away the debris and cleaning the floor etc.The job shall be complete & to the entire satisfaction of the	JOB	1		
G	Supply & fiving of Apage 6A - 11 1 0				
G	Supply & fixing of 4nos. 6A switches & sockets (Modular type c/w MS/GI box & cover plate) complete with computer point circuit wiring with 2x2.5sq.mm + 1x 1sq.mm stranded Cu. Single core Copper conductor (Finolex/Anchor/RPG) to be laid in PVC conduit 1" dia/vertical drops heavy duty laid & concealed in wall/ floor/panelling/partitions or above false ceiling as per requirement.	Per Node	8		
_					
	MAIN INCOMING PANEL & DISTRIBUTION				
	SITC of 100A Kit kats fuse unit 3nos in wooden patra complete with 100Amp. Neutral link complete in all respect as required.	Set	1		
	1 No for Metre				
В	1 no for Panel to Outer Side Of Wall (For Generator Connection) Main Incoming Panel				
	Supply, Installation, Testing & Commissioning of main distribution board panel fabricated of 18swg (powder coated) comprising of	Nos.	0		
	Indicator lamps 3 nos.				4.5
	Voltmeter & ammeter(one each)			- C	
	Rotary selector switches 2 nos for voltmeter & ammeter			-	
	Busbar (each of RYB +N) copper 100 amp each				
	125 Amp MCCB(Siemens/ L&T/ ABB/ Schnider) incoming 3P adjustable 25kA				
(Changeover TPN 100 amp for DG set (Havells/ ABB/ Sochomac)				
(Outgoing 63A 3P MCB's - 6 nos.				
	Outgoing 32Amp 2P MCB's - 6 nos.				
		1			
	Earth bus bar 25x5mm GI strip - 2nos. At the bottom.			-	

6	Supply Installation testing & commissioning of XLPE insulated Armoured Al.codutctor cable between main panel & DB's & generator of required thickness of approved make Skytone/ Havells based on the load assessment & confirmation of the same with architect. This rates include cost of lugs at both the ends					
	3.5 x50 sq.mm cable from Meter to Kit kat to the Pole (Aprrox - 20 mtr)	JOB	1			
	4c x20 sq.mm cable for LHS DB (Aprrox - 20 mtr)	JOB	1			
	4c x 20 sq.mm cable for RHS DB (Aprrox - 20 mtr)	JOB	1			
7	Supply, installtion, testing & commissioning of VTPN Db double door with MCB as incomer IP 42 complete in all respects for AC, PP and L & F as under - Siemens/ Hager/ Lagrand/ ABB					
A	RHS 6way VTPN db - Loaction RHS wall opposite Cash cabins (From entrance to Rear record room & Toilet area) - Siemens 8GB0406VRC or					
	Incomer - 63A 3P MCB 10kA adjustable neutral to be directly connected to neutral bus	Each	1			
	3no. 32A 1P-MCBs 10 KA - AC's - 2nos. RHS & 1rear 3no. 16A 1P-MCBs 10 KA - for single power points - 2 cash & 1 May I help You & 2nos. D/W					
	4nos. 10A 1P-MCBs 10 KA for L&F					
	4os. 6A 1P-MCBs 10 KA for L&F		-			
	Blanking Plates - 2no.					
	All connections to be terminated thru lugs					_
В	LHS 6way VTPN db - Loaction LHS wall behidn advance (From LHS LV Cash to Mgr Rm)- Siemens 8GB0406VRC or equivalent					
	Incomer - 63A 3P MCB 10kA adjustable neutral to be directly connected to neutral bus	Each	1			
	40. 32A 1P-MCBs 10 KA - AC's - 3nos. LHS & 1 Mgr Rm					
	4no. 16A 1P-MCBs 10 KA - for single power points - (LV cash, 2 CRE, 1Advance, 2 MR & 2 Router)					
	2nos. 10A 1P-MCBs 10 KA for L&F					
	2os. 6A 1P-MCBs 10 KA for L&F					
	Blanking Plates - 2no.					
	All connections to be terminated thru lugs		-			
8	Glow sign Board - Circuit wiring with 2x2.5sq.mm + 1x 1.0sq.mm stranded Cu. conductor (Finolex/Anchor/Skytone) to be laid in 19 mm PVC pipe heavy duty laid & concealed in wall/ floor/ panelling/ partitions or above false ceiling as per requirement. The rates should include the cost of all materials, labour, T&P, taxes & levies, scaffolding, shifting of furniture, carting away the debris and cleaning the floor etc. The job shall be complete & to the entire satisfaction of the Bank.	JOB	0			
	D. DADOWINA		-			
-	E - EARTHING Devel S (hypring of Dyel pine technology (Pine in Pine)					
9	For Main Panel - S/burying of Dual pipe technology (Pipe in Pipe) earthing electrode having GI 80mm O/D pipe with 25 micron coating, 3metres long. The space between two pipes to be filled with Highly conducive & Non corrosive chemical compound. The installation shall be thru earth auger. The vacant space between pipe & hole shall also be filled with compound all around. The job also includes S/F of GI strip clamp with two holes (with SS/GI bolts & nuts) on the electrode & taking two earthing leads of 25 x 5 mm GI strip (Assumed length of 10m - beyond 10m to be paid extra) upto Main panel complete in all respects with guaranteed E/N voltage of less than 3 volts and resistance less than 1 ohms. The distance between two earthing pits to be 10ft or more INCLUDING Earth wire 4 sq mm copper wire . Approx - 80 mtr (2 FOR BRANCH & 1 ATM)	Per Icn.	2	3	_ :+d	e st
10	F - FIXTURES & FITTINGS					

	A a Supplying and fixing Philips make 26W LED FLAT DANKS					
	a) Supplying and fixing Philips make 36W LED FLAT PANEL after disconnection of existing fitting 2'x2' size in grid type false ceiling, 600x600 suitable for recess mounting, CRCA sheet, asthetic looking, or eqv Philips/havells	Each	0			
-						
F	b) Supplying and fixing Philips make or eqv 10 W LED round type downlighter (Philips/ wipro /Jaguar)	Each	0			Ef
-						
	Supply installation testing and commissioning of 1*20watt Batten type tubular LED light fitting with LEDs, driver, diffuser, and housing complete in all respects in UPS room and record /wc/bath room /suitable place with complete in all respect with required color on need basis.		15			
D	S/F of angle holder for bulbs including cost of 11w CFL lamp for Toilets	Each	3			
-	i) Symple 9 in tell (i)					
E	i) Supply & installation of wall bracket fan 450 MM (Heavy duty/high speed) Make Bajaj/cropmton greaves/havells/Orient (to be supplied after consultation with architect/Electrical Engineer as per approved drawing)	Each	7			
F	g) Supply & fixing of the 1200 mm 48") Sweep Ceiling fan (Orient					
	PSPO/crompton greaves/havells) with downward rod(below false ceiling), canopy etc. including of PVC flexible copper wire.(white colour)(High speed) (Warranty Cerificate is necessary)with downward rod, circular boxes, ball sockets, ceiling plates, suitable arm bracket etc. including connection with wire)White colour (WITH REGULATOR)	Each	5			
G	Supply & Fixing of feach six for 10"			*		
	Supply & Fixing of fresh air fan 12" - Crompton Greaves/ Usha/ Khaitan/ Bajaj	Each	2			
Н	e) Supplying and fixing LED strip 3000 K 24 watt 5 mtr length with					
	driver (Philips or Havells or Cormpton)	SET	0			
11	H - TELEPHONE					
A						
	P/f Krone or equivalent box in the server room & out side of the Branch with a ten pair connecting strip for telephone with lock & key	Each	0			
В	10 Pair Cable with Constant S					
D	10 Pair Cable with Connection from main Panel to entrance of the Branch	JOB	0			
С	Supply & fixing on wall/ furniture/ partition recessed type non modular					
	telephone socket outlet (RJ-11) with mounting box & front plate complete with chase cutting, mending good etc. as required complete with Supply & laying of 2pair 0.61mm dia. PVC insulated telephone cables through 19mm dia rigid PVC conduit of suitable diameter as directed by the consultant from telephone junction box to telephone socket outlet including interconnection mending good etc. as required complete in all respects.	Each	0		4	. 43
-	Wireless Call Bell of Approved Quality (Orient, Sunshine)					
1)	Value of Authoriti Chianty (Circent Sunching)					
	I - DATA CABLING	No.	0			£*

A	Supply & Fixing of XL RJ 45 toolless information outlet with Duplex face plate with dual connectors Grey colour cat 6e including cost of supplying & laying CAT 6e (as directed by Architect from Server to Switch, Switch to computer I/O data socket as required complete in all respects) in 25mm dia rigid PVC conduit (including laying of GI draw wire complete with junction box, circular box, elbows, bends & other accessories as required by chase cutting on floor, wall, through partition or over false ceiling. The data cabling pipe should be laid at a minimum distance of 3ft from pipes laid down for power distribution) including interconnection with connectors as required complete in all respects.	Each	6			e e	
В	Supply & fixing of 7ft Grey colour Patch chord Giga speed Systimax/ D link make	Each	6				
С	Supply & fixing of 3ft Grey colour Patch chord Giga speed Systimax/ D link make	Each	6				
D	S/F of 24Port Jack Panel fully loaded systimex make	Each	1				
Е	S/F of 9 U wall mounted rack c/w fan etc as required	Each	1				
F	S/F of Cable Manager as required	Each	1				
	GRAND TOTAL AMOUNT (gst extra)					-	
	List of approved materials						
	Materials	Appr	roved	manufact	urers/sup	pliers	
1	MCCB	MD	S legra	ands, ABB	, GE, SIEN	MENS	
2	Changeover			sian/ HPL Standard			
3	Distribution board	MDS / Standard / Indo Asian / HPL					
4	MCB	MDS / Standard / Indo Asian / HPL					
5	Cable	Gloster / Rallison / Incab / CCI					
6	Copper wire			Finolex/a	nchor		
7	Switch / Socket / Call bell and accessories	A	nchor	/ Havells / Philip		DS	
8	Electrical Light Fittings / Fixtures Complete			Philip	s		
9	Wall Fan / Ceiling Fan / Exhaust Fan		1	Khaitan/H	lavells		